

# NASA TECH BRIEF

## *Marshall Space Flight Center*



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

### Central Control Element Expands Computer Capability

#### The problem:

Conventional computers do not have the flexibility of alternating between redundant processing and multiprocessing modes. Either one or the other mode is obtained, but the two are not available from one computer.

#### The solution:

Both modes can be obtained from one computer by using a new logic configuration. This configuration serves as a central control element (CCE) which can automatically alternate between a high-capacity multiprocessing mode and a high-reliability redundant mode using dynamic mode switching in real time.

#### How it's done:

The new CCE module is to be used in an automatically-reconfigurable modular system (ARMS) computer. The ARMS computer controlled by the CCE consists of multiple memories and central processing elements (CPE's), one or more input/output processors (IOP's), and a maintenance/status panel. These modules are standard computer building blocks. Each module contains internal fault detection logic, utilizing redundancy and error detecting and correcting codes.

The CCE distributes power and clock signals to ARMS modules, and it coordinates ARMS reconfiguration, either due to new assignments from the maintenance/status panel or in response to fault interrupts from other ARMS modules. The CCE consists of the following:

- Individual status controllers for each ARMS module to be controlled,
- Fault correlation logic,
- An overall program initiator and reconfiguration controller,

- Switching logic for power supplied to other modules,
- A crystal-controlled central clock source, and
- External interrupt routing logic.

The CCE has no internal-processing or main memory bus access capabilities. However, it is capable of utilizing CPE software or hardware to enhance its own hard-wired capabilities by means of interrupts.

At this time, the CCE is developed with T<sup>2</sup>L, small-scale integrated-circuit logic. Improved reliability will become available by using CMOS (complementary metal-oxide semiconductor), large-scale integration (LSI) technology. As proposed for ARMS, the CCE contains 1,174 gates which can be easily implemented in two or three LSI's.

#### Note:

Requests for further information may be directed to:

Technology Utilization Officer  
Marshall Space Flight Center  
Code AT01  
Marshall Space Flight Center, Alabama 35812  
Reference: B75-10103

#### Patent status:

Inquiries concerning rights for the commercial use of this invention should be addressed to:

Patent Counsel  
Marshall Space Flight Center  
Code CC01  
Marshall Space Flight Center, Alabama 35812

Source: R. A. Easton of  
Hughes Aircraft Co.  
under contract to  
Marshall Space Flight Center  
(MFS-23216)

Category: 02 (Electronics Systems)